

DESCRIPTION

PRIMER BB is an acrylic resin based, colored, plaster primer material used to increase adherence and to form an adhesion surface prior to plastering of gross concrete surfaces.

APPLICATION AREA

- Indoors and outdoors,
- In horizontal and vertical applications,
- In ceramic adhesive applications,
- To reduce the absorption of surfaces on walls and upholstery,
- For gypsum and cement based plaster applications,

Should be used as a primer to prevent the formation of cracks due to rapid water absorption and to increase the adherence.

SPECIAL FEATURES

- It can be easily applied in closed areas because it is odorless and water based.
- Creates a tight grip surface on smooth and smooth surfaces.
- Apply brush, roller.
- Color can be prepared.

CONSUMPTION AND APPLICATION

PRIMER BB lining is 0,150-0,200 kg / m².

Preparation of the surface;

Prior to application of PRIMER BB, the application surface must be free from adherence reducing substances such as dust, dirt and oil. The playing parts on the surface should be cleaned.

Application,

PRIMER BB is used with a brush or roll of water-thinned material, with a surface area of 1 m² and 0,150 kg of material. At application time and after application air temperature should be at least +50.

Cement based or plaster based plaster application can be done approximately 24 hours after application.

PACKING AND STORAGE

PRIMER BB is in 15 kg plastic buckets.

Shelf life is about 6 months in a cool environment.