

DESCRIPTION

QUARZTOP 100 surface hardeners are premixed ready to use product based on selection of hard aggregates, high quality cement and dispersive admixtures and inorganic pigments.

QUARZTOP 100 surface hardeners can be supplied in various colors; grey, red, green, yellow and inorganic pigments used are resistant to cement alkalis and light.

APPLICATION AREA

QUARZTOP 100 surface hardeners could be applied on; industrial floors designed light traffic factory floors, car service, car parks, supermarkets, hospitals, ramps, sport facilities, petroleum stations flooring surfaces realized in concrete.

PACKING AND STORAGE

QUARZTOP 100 surface hardener is packed in bags of 30 kg. If stored in covered in dry premises on pallets, has a shelf life of almost 6 months.

DOSAGE

QUARZTOP 100 surface hardeners can be applied 3-8 kg/m² in function of wear resistance of flooring.

APPLICATION

QUARZTOP 100 surface hardeners are product to be applied on shaking basis better in two successive hands. The first hand shake 2/3 of the total quantity on the fresh walking concrete. After the above mentioned trowelling, apply the remaining 1/3 of the product and repeat the toweling operation until desired finished the realized.

CURING

CEMIX CURING can be applied after surface is hardened and before the execution of the joint cut. The Cemix Curing maintains the humidity in the concrete during the first phase of curing, helping to obtain major mechanical resistance.